

## CONDUIT WHIPS

### Submittal Information

Part No 15801-15808  
Document No. SPEC15801  
Date 2020-02-05  
Revision 01

### General Properties

Material: A- Rubber: EPDM blend, a neoprene blend, or vinyl blend.  
Color: Black  
Max Loading capacity: 50 psi (pound per square inch)

### Applications

- Air condition unit hook up
- Heat pumps
- Pools, spas
- Outdoor lighting
- Motors and controls
- Solar panels

### Features

- 1 straight and 1 90 degree metallic or non-metallic connector. 90-degree connector is removable for straight connectors (Second straight connector not included).
- UL Listed Cable consists of insulated conductors inserted into a non-metallic conduit with zinc alloy connectors Be designed for reliable use as a connection between air conditioning unit and electrical power source.
- N/M UL Listed Cable consists of insulated conductors inserted into a non-metallic conduit with PVC connectors Be designed for reliable use as a connection between air conditioning unit and electrical power source.
- Whip is a labor-saving and convenient tool kit for A / C unit connection.
- Resists Corrosion, oil and water; Outdoor, sunlight resistant.
- Easy to use. Lower installation cost and a time saving convenience.
- UL and cUL Listed. The Seal proof Power Whip Assembly is assembled with all UL components. Designed for easy installation.
- Three distinct wire colors for ease of hook-up.

NOTE: Be sure purchase the correct sized conduit to your electrical box.riently.



Product	LENGTH	O.D.	CONNECTOR	WIRE SIZE
15801	4 "	1/2 "	Non-Metallic	#10 THHN
15802	6 "	1/2 "	Non-Metallic	#10 THHN
15803	4 "	3/4 "	Non-Metallic	#8 THHN
15804	6 "	3/4 "	Non-Metallic	#8 THHN
15805	4 "	1/2 "	Metallic	#10 THHN
15806	6 "	1/2 "	Metallic	#10 THHN
15807	4 "	3/4 "	Metallic	#8 THHN
15808	6 "	3/4 "	Metallic	#8 THHN



WARNING: Birth Defects, Reproductive Harm, and Cancer.  
[www.p65warnings.ca.gov](http://www.p65warnings.ca.gov).